

All Models Feature X TORQ® Engine Technology that Reduces Emissions 75%, Increases Fuel Economy 20% and Produces More Power and Torque.

| Model | CE760 | CE970 | CE1260 |
|--|---|------------------------|---------------------|
| ENGINE TYPE- X TORQ® | Air cooled-2-stroke | Air cooled-2 stroke | Air cooled-2 stroke |
| DISPLACEMENT | 4.5 cu in. (74cc) | 5.7 cu in. (94cc) | 7.3 cu in. (119cc) |
| MAXIMUM BLADE SPEED (No Load) | 5400 RPM | 5400 RPM | 4700 RPM |
| POWER | 5hp (3.7kW) | 6.4hp (4.8kW) | 7.8hp (5.8kW) |
| SMART CARB™ | Compensating carburetor produces full power in all cutting conditions – Standard on all models. | | |
| MOMENTARY CONTACT ON/OFF SWITCH | Standard | Standard | Standard |
| COMPRESSION RELEASE AND AIR PURGE | Standard | Standard | Standard |
| BIG GRIP “D” HANDLE DURA STARTER™ | Standard | Standard | Standard |
| FUEL LEVEL INDICATOR Shows Fuel Level at a Glance | Standard | Standard | Standard |
| AIR FILTRATION SYSTEM | Active Air Filtration™ delivers cleanest air possible to the Carburetor in all cutting conditions with K&N filter wraps to Protect filter in wet cutting operations – Standard on all models. | | |
| WATER KIT | Dust Handling System - | Standard on all models | |
| BLADE DIAMETER | 12 in (305mm) 14 in (355mm) | 14 in (355mm) | 16 in (400mm) |
| CUTTING DEPTH | 4 in (100mm) 5 in (127mm) | 5 in (127mm) | 6 in (154mm) |
| CUTTING BLADE | Cutters Edge Black Diamond Blade is Standard on All Models | | |
| ARBOR SIZE | 1 in (2.54cm) | 1 in (2.54cm) | 1 in (2.54cm) |
| REFLECTIVE LABELS | Standard on all models | | |
| ILLUMINATING HANDLES | FoxFire® Illuminating Handles glow in dark – Optional | | |
| SCRENCH TOOL & HOLDER | Standard | Standard | Standard |
| WEIGHT WITHOUT FUEL AND CUTTING EQUIPMENT | 12 in 20.7 lbs (9.4kg) | 25.1 lbs (11.4kg) | 32 lbs (14.4kg) |
| SOUND POWER LEVEL Lwa, dB(A) | 113 | 114 | 118 |
| SOUND PRESSURE LEVEL | 97 dB(A) | 116 dB(A) | 102 dB(A) |
| VIBRATIONS (m/s²) | | | |
| Front Handle Equivalent | 3.2/4.6 | 4.3/3.9 | 4.9/5.1 |
| Rear Handle Equivalent | 3.0/5.0 | 4.7/4.4 | 6.3/5.2 |

Cutters Edge
Division of Edge Industries, Inc
www.cuttersedge.com

PO Box 846 | 3855 23rd Street | Baker City, Oregon 97814 USA
Toll Free (US / Canada): 1-(800) 433-3716
Telephone: (541) 524-9999 International: +1-(541) 524-9999
Fax: 1-(541) 524-9996 Fax: +1 (541) 524-9996
Email: info@cuttersedge.com

Cutters Edge®
FIRE RESCUE SAWS

MULTI-CUT® H¹ Series
Rotary Rescue Saw



Use This Code to See
The X-Torq® Engine
In Action Now



Cutters Edge®
FIRE RESCUE SAWS

"NEXT GENERATION TECHNOLOGY" MULTI-CUT H¹ Series Rotary Rescue Saw

This new X TORQ® technology utilizes Dual Intakes that split the airflow into one fresh-air stream and one clean-air stream for the fuel-air mixture. The fresh-air intake forms a barrier that delays the fresh fuel mix from entering the engine while assisting in exhausting the burned gases. Then the fuel-air mixture enters the engine, resulting in more power, higher torque, 75% less emissions and 20% more fuel economy than conventional 2-stroke engines.

