

RM8

Electrically controlled turret



Description

The electrically controlled turret RM8 is the ideal bumper turret for industrial-, airport- and municipal vehicles due to its compact design.

Benefits

Flow rate

- up to 1.000 l/min at 10 bar (264 gal/min at 145 psi)
water or water-/foam respectively 20 kg/s (22 lbs/
sec) powder

Suitable for most extinguishing agents

- water
- water-foam mixture (non air aspirated)
- powder

Excellent throw range

- > 42m (138 ft) water

Simple operation


- The electrical control enables to control the horizontal and vertical movements as well as the spray adjustment and the control of the water flow with a joystick

Compact turret

- The turret is ideally suitable as bumper turret through it's small width

RM8

Elektrisch gesteuerter Werfer



Bumper turret for water-/foam



Powder turret



Bumper turret on ARFF



Joystick

Technical data

Drive	electric motors, manual emergency actuation via friction clutches
Rotation range	max. 270°
Swivel range	max. -30° up to +70°
Connection	flange DN50, vertical
Nozzle	O-stream nozzle
Nozzle adjustment	electric adjustment for full/spray jet
Powder nozzle	optional integrated: max. flow rate 20 kg/s (44 lbs/sec)
Electric	12 V or 24 V
Control	electrical control

Contact

Rosenbauer International AG
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

 www.facebook.com/rosenbauergroup

Text and illustrations are not binding. The illustrations may show optional extras only available at extra charge.
Rosenbauer retains the right to alter specifications and dimensions given herein without prior notice.

KR431
2013-06_RWeb