

# Compact gully sealing bags



- Good resistance to oil and chemicals
- Ready to use in transport case
- Withstands counterpressure of up to 2 m WC (2.9 psi)
- For gullies with diameters up to 80 cm (32 inch)



[www.vetter.de/ index.php? id=3324&site=vetter\\_emergency&lang=en](http://www.vetter.de/index.php?id=3324&site=vetter_emergency&lang=en)

## Reliably seal sewage systems and gullies.

With the Vetter compact gully sealing bag, you can take action immediately. Seal the gully together with the sewer inlet: ready to use on the spot, quick to put into position and easy to handle. The sealing bags withstand counterpressure of up to 2 m water column (2.9 psi) and can be inflated with the supplied compressed air cylinder. Seal gullies with a diameter of up to 80 cm (32 inch) the easy way.

### Compact set



#### Compact set

**1460001001**

- Compact gully sealing bag type, 30/50, 0.5 bar (7.25 psi)
- Inflation and safety fitting
- Compressed air cylinder 1 l / 200 bar (0.04 cu. ft. / 2,900 psi) (not filled)
- Transport case 600 x 400 x 220 mm (24 x 16 x 9 inch)

**Weight set: approx. 11.7 kg (25.8 lbs)**

## Emergency Pneumatics

### Technical data

- Working pressure: 0.5 bar (7.25 psi)
- Test pressure: 0.65 bar (9.4 psi)
- Test counterpressure: 2 m water column (2.9 psi)

| Product      | Art. no.   | Gully outlet<br>min. – max.<br>cm / inch | Cylinder-<br>length<br>cm / inch | Total-<br>length<br>cm / inch | Diameter<br>cm / inch | Air requirement,<br>at working<br>pressure<br>litres / cu.ft. | Weight,<br>approx.<br>kg / lbs |
|--------------|------------|------------------------------------------|----------------------------------|-------------------------------|-----------------------|---------------------------------------------------------------|--------------------------------|
| <b>30-50</b> | 1460000101 | 30-50<br>12-20                           | 41<br>16                         | 46<br>18,1                    | 29,5<br>11,6          | 128<br>4,5                                                    | 3,7<br>8,2                     |
| <b>50-80</b> | 1460001400 | 50-80<br>20-32                           | 41<br>16                         | 46<br>18,1                    | 45<br>17,7            | 426<br>15                                                     | 8,3<br>18,3                    |

### Accessories



#### In operation...

- Chemical leaks
- Floodings
- To seal gullies



#### Good reasons...

- Supplied compressed air cylinder (refillable) inflates two bags
- Inflation fitting can be uncoupled for repeat use
- Tether for lowering and securing bag



#### Guaranteed quality:

- Individually tested (with inspection seal)
- Resistant to ozone
- Good resistance to oil and chemicals

---

**Please contact us directly should you have any further questions concerning this product.**

#### Sales Germany

Phone.: +49 (0) 22 52 / 30 08-50

Fax: +49 (0) 22 52 / 30 08-70

E- Mail: [vetter.info@idexcorp.com](mailto:vetter.info@idexcorp.com)

#### Sales international

Phone.: +49 (0) 22 52 / 30 08-60

Fax: +49 (0) 22 52 / 30 08-71

E- Mail: [vetter.info@idexcorp.com](mailto:vetter.info@idexcorp.com)

#### Or find the nearest dealer under:

[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)

---