

Flange drain bag



- Completely covers the flange
- For lots of pipe connections
- For DN 50 (50 mm/1.9 inch) to DN 100 (100 mm/3.9 inch)
- Sealing pressure of 1 bar (14.5 psi)



www.vetter.de/vetter/emergency/en/Rescue+Products/Sealing+and+controlled+Drainage/Flange+drain+bag.html

Perfect fit for safe drainage at flanges.

Problems with leaky pipe connections? Make the task of sealing difficult leaks on all types of flanges easier for your team. Flanges are critical pipe sections and conventional sealing bags will rarely be effective here. Vetter flange drain bags cover the flange and pipe, reliably stop the leakage of hazardous liquids and at the same time allow you to drain off the liquid in a controlled and safe manner. The bags come in three sizes to cover all customary pipelines and flanges. Gel plates are included for convenient smoothing out of minor irregularities and unevenness on the pipe's surface.

It couldn't be simpler:

Place the bag around the flange and pipe, close the zip fastener along the entire length of the bag and inflate the sleeves. Immediately, everything is sealed and you can commence with controlled drainage of the liquid.

Flange drain bag sets



All sets described here include as standard components:

- Inflation hose 1.5 bar, 10 m, blue (21.75 psi, 32 ft.)
- Foot pump with safety valve 1.5 bar (21.75 psi)
- Acid drain hose, 5 m (16.4 ft.), with D suction coupling V4A
- Transport case 800 x 600 x 220 mm (32 x 24 x 9 inch)

- **DN 50 1500019600**
Flange drain bag DN 50, 1.5 bar (21.75 psi) and 4 sealing gel plates
- **DN 80 1500019900**
Flange drain bag DN 80, 1.5 bar (21.75 psi) and 4 sealing gel plates
- **DN 100 1500023700**
Flange drain bag DN 100, 1.5 bar (21.75 psi) and 6 sealing gel plates

Technical data

Uniform sealing pressure of 10 m WC (14.5 psi).

- Working pressure: 1.5 bar (21.75 psi)
- Test pressure: 1.95 bar (28.5 psi)

Product	Art. no.	External size Øcm / Øinch	Length cm / inch	Air requirement, at working pressure litres / cu.ft.	Weight of individual bag, approx. kg / lbs	Weight of set, approx. kg / lbs
DN 50	1500006600	21,0 8,3	90,0 35,0	1,25 0,1	3,1 6,8	17,8 39,2
DN 80	1500019200	21,0 8,3	90,0 35,0	1,25 0,1	3,1 6,8	17,8 39,2
DN 100	1500023400	25,0 9,8	92,0 36,0	1,25 0,1	3,5 7,7	18,4 40,1

Accessories

- Inflation hoses 1.5 bar (21.75 psi)
- Controllers 1.5 bar (21.75 psi)
- Foot pump 1.5 bar (21.75)
- Inflation with cylinder
- Inflation with alternative air source



In operation...

- Sealing and controlled drainage of hazardous substances
- On flanges and pipe connections



Good reasons...

- Gas- and liquid- tight zip fastener
- Acid drain hose with shut- off unit
- Gel plates supplied to smooth out unevenness included



Guaranteed quality:

- Individually tested (with inspection seal)
- Stainless steel connections

Please contact us directly should you have any further questions concerning this product.

Sales Germany
Phone.: +49 (0) 22 52 / 30 08-50
Fax: +49 (0) 22 52 / 30 08-70
E- Mail: vetter.info@idexcorp.com

Sales international
Phone.: +49 (0) 22 52 / 30 08-60
Fax: +49 (0) 22 52 / 30 08-71
E- Mail: vetter.info@idexcorp.com

Or find the nearest dealer under:
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)
