

High- pressure leak sealing system



- Innovation from Vetter
- Sealing in difficult- to- access places
- For leaks in pipes with diameter up to 20 cm (8 inch)
- For counterpressure up to 9 bar (130 psi)



www.vetter.de/vetter_emergency/en/Rescue+Products/Sealing+leaks/High_pressure+leak+sealing+system.html

Intelligent hose system for complicated pipe leaks.

In close collaboration with Henkel KGaA, Dusseldorf, Vetter has developed an intelligent sealing hose system. Now you can effortlessly access even hard- to- reach leaks in narrow or unevenly shaped piping systems.

The flexible hoses fit perfectly even over complicated leaks, e.g. at T- pieces, pipe bends, connecting branches and welded seams. The hoses are inflated in seconds and withstand counterpressure of up to 9 bar (130.5 psi).

Premium set



Premium set 1500015800

With the premium set, you are equipped for every eventuality. It can be used with several different sized pipes and to seal several leaks at the same time. The set contains 3 sealing plates and can thus be used with a wide range of hazardous materials.

- Sealing hose 1.5 m, 2.5 m, 3.5 m (59 inch, 98 inch, 138 inch)
- Inflation valve and inflation hose
- Pressure regulator 200 / 300 bar (2,900 / 4,350 psi)
- 3 sealing plates NBR, EPDM, FKM, 15 x 21 cm (6 x 8 inch)
- Bleed valve
- Transport case 600 x 400 x 220 mm (24 x 16 x 9 inch)

Weight set: approx. 12.3 kg (27.1 lbs)

Basic set



Basic set 1500019000

The basic set contains 1 hose and 1 sealing plate. The pressure regulator is not included.

- Sealing hose 2.5 m (98 inch)
- Inflation valve and inflation hose
- Sealing plate FKM 15 x 21 cm (6 x 8 inch)
- Bleed valve
- Transport case 400 x 300 x 220 mm (16 x 12 x 9 inch)

Weight set: approx. 7.3 kg (16.1 lbs)

Emergency Pneumatics

Technical data

Uniform counterpressure of 9 bar (130.5 psi).

- Working pressure: 10 bar (145 psi)
- Test pressure: 16 bar (232 psi)

Product	Art. no.	Air requirement, at working pressure litres / cu.ft.	Temperature °C / °F	Weight, approx. kg / lbs
1.5 m Sealing hose	1500015901	8,1 0,3	-30 - +80 -22 - +176	1,1 2,5
2.5 m Sealing hose	1500016001	14,6 0,5	-30 - +80 -22 - +176	1,4 3,0
3.5 m Sealing hose	1500016101	20,4 0,7	-30 - +80 -22 - +176	1,8 3,9

Accessories

- Inflation hoses 1.5 bar (21.75 psi)
- Controllers 1.5 bar (21.75 psi)
- Foot pump 1.5 bar (21.75)
- Inflation with cylinder
- Inflation with alternative air source



In operation...

- Can be used on T- pieces, pipe bends or difficult- to- access connecting branches
- For leaks in pressure lines or fittings



Good reasons...

- Universally usable and easy to use
- For counterpressure up to 9 bar (130.5 psi)
- Additional sealing plates for extra stability
- Sealing hoses with electrostatic conductivity (DIN ISO 8031/8.97)



Guaranteed quality:

- Individually tested (with inspection seal)
- Earth connection to sealing hose coupling on both sides
- All metal parts made of stainless steel

Please contact us directly should you have any further questions concerning this product.

Sales Germany
Phone.: +49 (0) 22 52 / 30 08-50
Fax: +49 (0) 22 52 / 30 08-70
E- Mail: vetter.info@idexcorp.com

Sales international
Phone.: +49 (0) 22 52 / 30 08-60
Fax: +49 (0) 22 52 / 30 08-71
E- Mail: vetter.info@idexcorp.com

Or find the nearest dealer under:
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)
