

Ultra Flat Bags S.Tec 145 psi



- 25 % more performance*
- Insertion height only 1.6 cm (0.6 inch)
- Ready to use in seconds
- Reflective markings



www.vetter.de/vetter_emergency/en/Rescue+Products/Lifting+bags/Ultra+Flat+Bags+S_Tec+145+psi.html

The unbeatably flat first- aider of the S.Tec series.

The S.Tec series is supplemented by a super- flat first- aider. With their super- flat insertion height of only 1.6 cm (0.6 inch), Vetter ultra flat bags are the ideal first- aider at the rescue site, fitting into the smallest of gaps. They exert their strength in the most confined spaces and make room for other rescue tools. Thanks to their low air requirement and extreme ease of use, Vetter ultra flat bags are ready to use in seconds. In short: an indispensable tool in a wide range of situations.

* when compared with conventional 8 bar (116 psi) lifting bags of the same size

Emergency Pneumatics

Technical data

Unrivalled low insertion height of only 1.6cm* (0.6 inch).

- Working pressure: 10 bar (145 psi)
- Test pressure: 16 bar (232 psi)
- Burst pressure, at least.: 40 bar (580 psi)

*around valve +6mm (0.2inch)

Product	Art. no.	Lifting power, max. t / US tons	Lifting height, max. cm / inch	Size cm / inch	Air requirement, at working pressure litres / cu.ft.	Weight, approx. kg / lbs
UF 1 S.Tec	1315006000	1,1 1,3	7,5 3,0	14 x 13 5,5 x 5,1	3,85 0,14	0,4 0,9
UF 4 S.Tec	1315006100	3,8 4,2	12,0 4,7	25,5 x 20 10 x 7,9	24,75 0,88	1,0 2,2
UF 7 S.Tec	1315006200	7 7,7	16,5 6,5	29,5 x 29,5 11,6 x 11,6	48,4 1,71	1,7 3,7
UF 12 S.Tec	1315005900	11,6 12,8	20,3 8,0	37 x 37 14,6 x 14,6	92,95 3,29	2,4 5,3

Accessories

- Inflation hoses 10 bar (145 psi)
- Shut- off units 10 bar (145 psi)
- Controllers 10 bar (145 psi)
- Inflation with cylinder
- Inflation with alternative air source



In operation...

- Freeing trapped persons
- Preliminary measures
- Freeing trapped limbs
- Enlarging smallest openings
- At accidents



Good reasons...

- Super- flat insertion height of only 1.6 cm (0.6 inch)*
- Flexible and easy to use
- Aramid- reinforced



Guaranteed quality:

- Individually tested (with inspection seal)
- Safety factor greater than 4:1
- Complies with EN 13731
- 3- year guarantee

Please contact us directly should you have any further questions concerning this product.

Sales Germany
Phone.: +49 (0) 22 52 / 30 08-50
Fax: +49 (0) 22 52 / 30 08-70
E- Mail: vetter.info@idexcorp.com

Sales international
Phone.: +49 (0) 22 52 / 30 08-60
Fax: +49 (0) 22 52 / 30 08-71
E- Mail: vetter.info@idexcorp.com

Or find the nearest dealer under:
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)
