

# Permanent Aspirator (PA)



- For suctioning and pumping out liquids
- Pump can be switched on separately
- Capacity of 100 l (3.5 cu. ft.)
- Trolley for round container

[www.vetter.de/vetter\\_emergency/en/Rescue+Products/Oil+and+water+aspirators/Permanent+Aspirator+%28PA+%29-p-4511.html](http://www.vetter.de/vetter_emergency/en/Rescue+Products/Oil+and+water+aspirators/Permanent+Aspirator+%28PA+%29-p-4511.html)

## The specialist for suctioning and pumping out liquids

Vetter will not leave you out in the rain. Our high-performance aspirator range was specifically developed for fire services. Connect a fire hose to the permanent aspirators to suction the water or liquids left in deep cellars or other rooms after flooding, storms, burst pipes or fires quickly and easily - and pump them out at the same time!

As a hazardous materials specialist with many years of practical experience, Vetter is well acquainted with your needs. That is why we manufacture the collection containers of our oil and water aspirators using sturdy glass-fibre-reinforced polyester, thus guaranteeing excellent resistance to chemicals. To ensure your safety, all appliances have spark suppression and are also completely earthed from the suction pipe to the cable.

## Emergency Pneumatics

### Technical data

#### Information to the motor head

- Current consumption: 4.6 Ampere (amps)
- Power consumption: 1000 Watt
- Voltage: 240/50/60 V/ Hz

#### Information to the pump

- Flow rate of pump: 260 l/ min. (9.2 cu.ft/ min.)
- Pumping height: 11 m (36 ft.)
- Current consumption: 3.4 Ampere (amps)
- Power consumption: 800 Watt
- Voltage: 240/50 V/ Hz

Product	Art. no.	Suction power air litres / min. / cu.ft. / min.	Suction power water litres / min. / cu.ft. / min.	Negative pressure mm WS / psi	Capacity collection containers litres / cu. ft.	Dimensions (L x W x H) cm / inch	Weight of set, approx. kg / lbs	Förderleistung Pumpe litres / min. / cu.ft. / min.
PA	2210001303	3030 107	160 5,7	2392 3,5	100 3,53	86 x Ø 62 34 x Ø 25	35 77	260 9,2

### Accessories

- Adapter Suction hose Aspirators incl. Coupling Storz 38
- Suction hose, 6 m, oil resistant, incl. curved connecting pipe
- Suction pipe, stainless steel (2 parts)
- Ground nozzle, 370 mm
- Narrow space nozzle
- Exhaust nozzle for Decon- tub (optional)
- Plug- in earth leakage circuit breaker IP 54 (optional)
- Connector to C 52 / 38 mm (optional)
- Shut- off unit Storz C (optional)



#### In operation...

- Floods and storms
- Accidents, pipe bursts and fires
- To suction foaming liquids
- To suction binding agents, e.g. after traffic accidents



#### Good reasons...

- Compared to other types of plastic, GFRP has very good resistance to chemicals
- Sturdy design
- Transparent container (makes liquid level visible)
- Container can easily be replaced



#### Guaranteed quality:

- Verifiably tested (inspection seal)
- Aspirator: Protection class IP 44 (splash- proof)
- Protective plug IP 68 (pressure water- proof)

---

**Please contact us directly should you have any further questions concerning this product.**

Sales Germany  
Phone.: +49 (0) 22 52 / 30 08-50  
Fax: +49 (0) 22 52 / 30 08-70  
E- Mail: [vetter.info@idexcorp.com](mailto:vetter.info@idexcorp.com)

Sales international  
Phone.: +49 (0) 22 52 / 30 08-60  
Fax: +49 (0) 22 52 / 30 08-71  
E- Mail: [vetter.info@idexcorp.com](mailto:vetter.info@idexcorp.com)

**Or find the nearest dealer under:**  
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)

---